

Product information | TECHNICAL DATA SHEET

MATT FIXER LACQUER

400 ml, 10.2 Oz, 289 g.

GENERAL DESCRIPTION

Clearcoat, non-yellowing, fast drying, matte fixative. Ideal as a fixative and protective coat on objects used indoors.

FEATURES

- Very fast drying.
- Excellent matt finish.
- Not weather or water resistant.
- Easy application for protecting different artistic techniques.

APPLICATIONS

Recommended for use in the fine arts for protecting pastel, pencil, watercolor, and charcoal drawings, and when a protective matte coat is required.

INSTRUCTIONS FOR USE

- Shake the aerosol well before using, approximately for one minute after hearing the sound of the mixer.
- Apply 1-3 coats of the product depending on the material that needs protection. Do a test prior to doing the final coat. Depending on the thickness of the layer applied, it may slightly whiten the surface's original color.
- For best results apply in thin layers. Three thin layers are always better than one thick one, and may be repainted within ten minutes with the same lacquer.
- Turn the aerosol upside down to clean out the valve after use. If the nozzle becomes blocked replace it with a new one.
- Never apply to equipment that is plugged in and use in well ventilated areas.
- Request safety datasheets.

PHYSICAL PROPERTIES

Color:	Transparent
Shine 60°:	>10 % matte
Dry to the touch (ASTM D-1640 ISO 1517):	10'
Completely dry (ASTM D-1640 ISO 1517):	20'
Thickness of dry layer (ASTM D-823 ISO 2808):	15 µ/capa
Theoretical yield (pintado en continuo):	2 m ²
Thinner:	Alcohol Etilic / IPA
Product life:	(Well Stored) 5 Years
Recoating:	After 15' minutes
Condition for application:	T° min 8°C
	T° surface 5°C
	Humidity max. 85% R.H.P.

*The adhesion tests were done on PP (EPDM modified). Last revision's date: 31/01/2017

CAUTION



APPEARANCE



LABEL



Matt Fixer Lacquer

CAP SYSTEM



Soft Cap
Medio- Grueso

PACKAGING

Nominal capacity: 400 ml.
Heat resistance of packaging: <50°C
Propellant: DME

Box (6 units)
205 X 140 X 200 mm.

